





United States Patent and Trademark Office



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER OF PATENTS AND TRADEMARKS Washington, D.C. 20231 www.uspto.gov

APPLICATION NO.	FIL	ING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/889,378	07	7/16/2001	Morio Yoshimoto	1163-0346P	2948
2292	7590	03/14/2003			
BIRCH STEWART KOLASCH & BIRCH PO BOX 747 FALLS CHURCH, VA 22040-0747	EXAMINER				
•				HOOSAIN	ALLAN
FALLS CHU	RCH, VA	22040-0747			
				ART UNIT	PAPER NUMBER
				2645	
			DATE MAILED: 03/14/2003		

Please find below and/or attached an Office communication concerning this application or proceeding.

•,		,	
		Application No.	Applicant(s)
	•	09/889,378	YOSHIMOTO ET AL.
	Office Action Summary	Examiner	Art Unit
		Allan Hoosain	2645
Period fo	The MAILING DATE of this communication a	appears on the cover sheet with the c	correspondence address
A SH THE - Exte after - If the - If NC - Failu - Any	ORTENED STATUTORY PERIOD FOR REF MAILING DATE OF THIS COMMUNICATION nsions of time may be available under the provisions of 37 CFR SIX (6) MONTHS from the mailing date of this communication. It is period for reply specified above is less than thirty (30) days, a reply period for reply is specified above, the maximum statutory period to reply within the set or extended period for reply will, by state reply received by the Office later than three months after the mailed patent term adjustment. See 37 CFR 1.704(b).	N. 1.136(a). In no event, however, may a reply be tireply within the statutory minimum of thirty (30) day od will apply and will expire SIX (6) MONTHS from tute, cause the application to become ABANDONE	nely filed /s will be considered timely. the mailing date of this communication. ED (35 U.S.C. § 133).
1)⊠	Responsive to communication(s) filed on 19	9 September 2001 .	
2a)□	This action is FINAL . 2b)⊠	This action is non-final.	
3)□	Since this application is in condition for allo closed in accordance with the practice und ion of Claims		
·		ion	
4)[Claim(s) <u>1-20</u> is/are pending in the application	,	
ح√□	4a) Of the above claim(s) is/are withd	rawn from consideration.	
	Claim(s) is/are allowed.		
_	Claim(s) <u>1-20</u> is/are rejected.		-
7)∐	Claim(s) is/are objected to.	d/or alastian requirement	
•	Claim(s) are subject to restriction and ion Papers	a/or election requirement.	
· · · —	The specification is objected to by the Exami	ner.	
-	The drawing(s) filed on 19 September 2001 is		to by the Examiner.
,—	Applicant may not request that any objection to		
11)[The proposed drawing correction filed on	is: a)□ approved b)□ disappro	oved by the Examiner.
	If approved, corrected drawings are required in	reply to this Office action.	
12)	The oath or declaration is objected to by the	Examiner.	
Priority	under 35 U.S.C. §§ 119 and 120		
13)⊠	Acknowledgment is made of a claim for fore	ign priority under 35 U.S.C. § 119(a	a)-(d) or (f).
a)	☑ All b)☐ Some * c)☐ None of:		
	1.⊠ Certified copies of the priority docume	ents have been received.	
	2. Certified copies of the priority docume	ents have been received in Applicat	ion No
* (3. Copies of the certified copies of the properties of the propert	Bureau (PCT Rule 17.2(a)).	-
	Acknowledgment is made of a claim for dome	•	
	a) The translation of the foreign language Acknowledgment is made of a claim for dome		
Attachmer	•		
2) Notic	ce of References Cited (PTO-892) ce of Draftsperson's Patent Drawing Review (PTO-948) mation Disclosure Statement(s) (PTO-1449) Paper No(s	5) Notice of Informal	ry (PTO-413) Paper No(s) Patent Application (PTO-152)

U.S. Patent and Trademark Office PTO-326 (Rev. 04-01)

Art Unit: 2645

DETAILED ACTION

Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

2. Claims 1-5, 7-13 and 17-20 are rejected under 35 U.S.C. 102(e) as being anticipated by Shaffer '490 (US 5,995,490).

As to Claim 1, with respect to Figures 1-2, **Shaffer '490** teaches a data communication device comprising:

a line state monitoring unit, 40, for detecting a line state relating to transmission quality in a communication line and producing line state information indicating the line state (Figure 1, label 36 and Col. 6, lines 1-10); and

a transmission control unit, 36, having a plurality of operation modes corresponding to a plurality of error tolerance levels different from each other, for selecting a specific operation mode from the operation modes according to the line state information produced by the line state monitoring unit and performing a transmission control for transmission data, which is planned to

Art Unit: 2645

be sent out to the communication line, according to the specific operation mode (Col. 4, lines 24-37).

As to Claim 2, **Shaffer '490** teaches a data communication device according to claim 1, wherein the specific operation mode is changed to another operation mode by the transmission control unit in response to the change of the line state indicated by the line state information during the transmission of the data without suspending the transmission of the data, and the transmission control is performed for the transmission data according to the changed operation mode by the transmission control unit (Figure 2, label 58,66).

As to Claim 3, **Shaffer '490** teaches a data communication device according to claim 1, wherein the transmission control unit has a plurality of data multiplexing methods corresponding to the operation modes, a specific multiplexing method is selected from the multiplexing methods by the transmission control unit according to the line state information produced by the line state monitoring unit, and pieces of transmission data, which are planned to be sent out to the communication line, are multiplexed with each other to a stream of multiplexed transmission data according to the specific multiplexing method (Col. 4, line 58 through Col. 5, line 3 and Col. 6, lines 30-40).

As to Claim 4, **Shaffer '490** teaches a data communication device according to claim 1, wherein the specific operation mode is changed to another operation mode corresponding to a high error tolerance level by the transmission control unit according to the line state information in cases

Art Unit: 2645

Page 4

where the line state information indicates a deteriorated line state, and the specific operation mode is changed to another operation mode corresponding to a low error tolerance level by the transmission control unit according to the line state information in cases where the line state information indicates an ameliorated line state (Col. 6, lines 30-45 and 56-65).

As to Claim 5, **Shaffer '490** teaches a data communication device according to claim 1, further comprising:

an operation mode change request receiving unit for receiving an operation mode change request from a second data communication device and sending the operation mode change request to the transmission control unit to make the transmission control unit perform the transmission control for the transmission data according to a particular operation mode indicated by the operation mode change request (Col. 6, lines 55-45 and 56-65).

As to Claim 7, **Shaffer '490** teaches a data communication device according to claim 1, further comprising:

a line interface for receiving and sending the transmission data to/from the communication line,

wherein the transmission control unit controls the line interface to increase a data transfer rate for data sending while decreasing a data transfer rate for data reception by a degree of the increase of the data transfer rate for data sending in cases where the specific operation mode is changed to a particular operation mode corresponding to a high error tolerance level in the

Art Unit: 2645

transmission control unit to perform the transmission control for the transmission data sent out to the communication line according to the particular operation mode (Col. 6, lines 55-65).

As to Claim 8, **Shaffer '490** teaches a data communication device according to claim 1, further comprising:

a line interface for receiving and sending the transmission data from/to the communication line,

wherein the transmission control unit controls the line interface to decrease a data transfer rate for data sending while increasing a data transfer rate for data reception by a degree of the decrease of the data transfer rate for data sending in cases where the specific operation mode is changed to a particular operation mode corresponding to a low error tolerance level in the transmission control unit to perform the transmission control for the transmission data sent out to the communication line according to the particular operation mode (Col. 6, lines 55-65).

As to Claim 9, with respect to Figures 1-2, **Shaffer '490** teaches a data communication device comprising:

a line state monitoring unit for detecting a line state relating to transmission quality in a communication line and producing line state information indicating the line state (Figure 1);

a transmission control unit, having a plurality of operation modes corresponding to a plurality of error tolerance levels different from each other, for selecting a specific operation mode from the operation modes according to the line state information produced by the line state

Art Unit: 2645

monitoring unit and performing a transmission control for transmission data, which is sent out to the communication line or is received through the communication line, according to the specific operation mode (Col. 4, line 58 through Col. 5, line 3); and

an operation mode change request outputting unit for requesting of a second data communication device, with which communication is performed through the communication line, that an operation mode selected in the second data communication device is changed to the specific operation mode selected by the transmission control unit (Col. 6, lines 30-45).

As to Claim 10, **Shaffer '490** teaches a data communication device according to claim 9, wherein the request of the operation mode change request outputting unit to the second data communication device is performed during the sending or reception of the transmission data without suspending the sending or reception of the transmission data (Col. 6, lines 30-45 and Col. 5, lines 30-42).

As to Claim 11, **Shaffer '490** teaches a data communication device according to claim 9, wherein the transmission control unit has a plurality of data multiplexing methods corresponding to the operation modes, a specific multiplexing method is selected from the multiplexing methods by the transmission control unit according to the line state information produced by the line state monitoring unit, and the operation mode change request outputting unit requests the second data communication device, during the transmission of the data without suspending the transmission of the data, to select the specific multiplexing method (Col. 4, lines 1-10 and Col. 5, lines 16-34).

Page 7

Application/Control Number: 09/889,378

Art Unit: 2645

As to Claim 12, **Shaffer '490** teaches a data communication device according to claim 9, wherein the operation mode change request outputting unit requests the second data communication device to change the specific operation mode to an operation mode corresponding to a high error tolerance level in cases where the line state information produced by the line state monitoring unit indicates a deteriorated line state, and the operation mode change request outputting unit requests the second data communication device to change the specific operation mode to an operation mode corresponding to a low error tolerance level in cases where the line state information produced by the line state monitoring unit indicates an ameliorated line state (Col. 6, lines 30-45).

As to Claim 13, **Shaffer '490** teaches a data communication device according to claim 9, further comprising:

an operation mode change request receiving unit for receiving an operation mode change request from the second data communication device, and sending the operation mode change request to the transmission control unit to make the transmission control unit perform the transmission control for the transmission data, which is received through the communication line or is sent out to the communication line, according to a particular operation mode indicated by the operation mode change request (Col. 6, lines 30-45).

As to Claim 17, **Shaffer '490** teaches a data communication device according to claim 9, further comprising:

Art Unit: 2645

a line interface for receiving and sending the transmission data from/to the communication line, wherein the transmission control unit controls the line interface to increase a data transfer rate for data sending while decreasing a data transfer rate for data reception by a degree of the increase of the data transfer rate for data sending, in cases where the specific operation mode is changed to a particular operation mode corresponding to a high error tolerance level in the transmission control unit to perform the transmission control for the transmission data sent out to the communication line according to the particular operation mode, and to increase a data transfer rate for data reception while decreasing a data transfer rate for data sending by a degree of the increase of the data transfer rate for data reception in cases where the specific operation mode is changed to a particular operation mode corresponding to a high error tolerance level in the transmission control unit to perform the transmission control for the transmission data received through the communication line according to the particular operation mode (Col. 6, lines 56-65 and Col. 7, lines 1-16).

As to Claim 18, **Shaffer '490** teaches a data communication device according to claim 9, further comprising:

a line interface for receiving and sending the transmission data from/to the communication line, wherein the transmission control unit controls the line interface to decrease a data transfer rate for data sending while increasing a data transfer rate for data reception by a degree of the decrease of the data transfer rate for data sending, in cases where the specific operation mode is changed to a particular operation mode corresponding to a low error tolerance level in the transmission control unit to perform the transmission control for the transmission

Art Unit: 2645

data sent out to the communication line according to the particular operation mode, and to decrease a data transfer rate for data reception while increasing a data transfer rate for data sending by a degree of the decrease of the data transfer rate for data reception in cases where the specific operation mode is changed to a particular operation mode corresponding to a low error tolerance level in the transmission control unit to perform the transmission control for the transmission data received through the communication line according to the particular operation mode (Col. 6, lines 56-65 and Col. 7, lines 1-16).

As to Claim 19, **Shaffer '490** teaches a data communication device according to claim 13, further comprising:

a line interface for receiving and sending the transmission data from/to the communication line (Figure 1),

wherein the operation mode change request receiving unit further receives a data rate change request from the second data communication device, the operation mode change request receiving unit sends the data rate change request to the transmission control unit, the transmission control unit controls the line interface to increase a data transfer rate for data sending while decreasing a data transfer rate for data reception by a degree of the increase of the data transfer rate for data sending according to the data rate change request, in cases where the specific operation mode is changed to a particular operation mode corresponding to a high error tolerance level in the transmission control unit according to the operation mode change request to perform the transmission control for the transmission data sent out to the communication line according to the particular operation mode, and the transmission control unit controls the line

Art Unit: 2645

interface to increase a data transfer rate for data reception while decreasing a data transfer rate for data sending by a degree of the increase of the data transfer rate for data reception according to the data rate change request in cases where the specific operation mode is changed to a particular operation mode corresponding to a high error tolerance level in the transmission control unit according to the operation mode change request to perform the transmission control for the transmission data received through the communication line according to the particular operation mode (Col. 6, lines 30-45, 56-65 and Col. 7, lines 1-16).

As to Claim 20, Shaffer '490 teaches a data communication device according to claim 9, wherein the operation mode change request outputting unit requests the second data communication device to increase a data transfer rate for data sending while decreasing a data transfer rate for data reception by a degree of the increase of the data transfer rate for data sending, in cases where the operation mode change request outputting unit requests the second data communication device to change the specific operation mode to a particular operation mode corresponding to a high error tolerance level in the transmission control unit according to the operation mode change request to perform the transmission control for the transmission data sent out to the communication line according to the particular operation mode, and the operation mode change request outputting unit requests the second data communication device to increase a data transfer rate for data reception while decreasing a data transfer rate for data sending by a degree of the increase of the data transfer rate for data reception in cases where the operation mode change request outputting unit requests the second data communication device to change the specific operation mode to a particular operation mode corresponding to a high error

Application/Control Number: 09/889,378 Page 11

Art Unit: 2645

tolerance level in the transmission control unit according to the operation mode change request to perform the transmission control for the transmission data received through the communication line according to the particular operation mode (Col. 6, lines 30-45, 56-65 and Col. 7, lines 1-16).

Claim Rejections - 35 USC § 103

- 3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 4. This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).
- 5. Claims 6, 14-16 are rejected under 35 U.S.C. 103(a) as being unpatentable over **Shaffer '490** in view of **Shaffer '668** (US 5,898,668).

As to Claims 6,14-16, **Shaffer** teaches a data communication device according to claim 1, further comprising:

Art Unit: 2645

a line interface, connected with the communication line, for sending the transmission data to the communication line (Figure 1, label 30),

wherein the transmission control unit controls the line interface connected with the line interface, in cases where the specific operation mode corresponds to a high error tolerance level, and in cases where the specific operation mode is changed to a low error tolerance level;

Shaffer '490 does not teach the following limitation:

"add a new communication line" and "disconnect the new communication line"

However, it is obvious that **Shaffer '490** suggests the limitation. This is because Shaffer '490 teaches connection to PSTN using one or more links (Figure 1 and Col. 3, lines 22-26). **Shaffer '668** teaches switch mode to different lines to enable QOS service levels (Figures 3-4 and Col. 8, lines 41-64). Having the cited art at the time the invention was made, it would have been obvious to one of ordinary skill in the art to add switch mode capability to **Shaffer '490** invention for interconnection to communication lines as taught by **Shaffer '668** invention in order to provide QOS requirements.

Conclusion

6. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Wan et al. (US 6,529,475) teach a system for reducing congestion in real-time multimedia communications.

Galand et al. (US 6,424,624) teach maintaining quality of service using different connections.

Art Unit: 2645

Focsaneanu et al. (US 5,610,910) teach multiplexing different communications on a single communication line.

7. Any response to this action should be mailed to:

Commissioner of Patents and Trademarks Washington, D.C. 20231 or faxed to:

(703) 872-9314, (for formal communications intended for entry)

Or:

(703) 306-0377 (for customer service assistance)

Hand-delivered responses should be brought to Crystal Park II, 2121 Crystal Drive, Arlington. VA., Sixth Floor (Receptionist).

Any inquiry concerning this communication or earlier communications from the examiner should be directed to **Allan Hoosain** whose telephone number is (703) 305-4012. The examiner can normally be reached on Monday to Friday from 7 am to 5:30 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, **Fan Tsang**, can be reached on (703) 305-4895.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the Group receptionist whose telephone number is (703) 305-3900.

Allan Hoosain Primary Examiner

3/7/03